

Contents of L^AT_EX's Tools Bundle

| | |
|---------------------|---|
| afterpage: | Place text after the current page. |
| array: | Extended versions of the environments <code>array</code> , <code>tabular</code> and <code>tabular*</code> . |
| bm: | Access bold math symbols. |
| calc: | Infix arithmetic expressions. Contributed to the distribution by Kresten Krab Thorup and Frank Jensen. |
| dcolumn: | Alignment on <i>decimal points</i> in tabular entries. Requires <code>array</code> . |
| delarray: | Adds <i>large delimiters</i> around arrays. Requires <code>array</code> . |
| enumerate: | Extended version of the <code>enumerate</code> environment. |
| fileerr: | Suite of small files which may be used to control T _E X's missing file error loop. |
| fontsmpl: | Package and test file for producing <i>font samples</i> |
| ftnright: | Place footnotes in the right hand column in two-column mode. |
| hhline: | Finer control over horizontal rules in tables. Requires <code>array</code> . |
| indentfirst: | Indent the first paragraph of sections etc. |
| layout: | Produces an overview of the layout of the current document. |
| longtable: | Multipage tables. (Does not require <code>array</code> , but uses the extended features if both are loaded.) |
| multicol: | Typeset text in columns, with the length of the final columns <i>balanced</i> . |
| rawfonts: | Preload fonts under the old internal font names of L ^A T _E X2.09. Not recommended for new packages, but may help when updating old files. |
| showkeys: | Draft mode showing the <i>keys</i> used by <code>\label</code> , <code>\ref</code> , <code>\cite</code> etc. |
| somedefs: | Selective handling of package options. (Used in <code>rawfonts.sty</code> .) |
| tabularx: | Defines <code>tabularx</code> environment (similar to <code>tabular*</code>) but modifies column widths, not inter-column space, to achieve a desired table width. |
| theorem: | Flexible definition of <i>theorem-like</i> environments. |
| trace: | The package helps to suppress and to control the amount of tracing output (<code>\tracingall</code>) by taming <code>calc</code> and making NFSS less noisy. |
| varioref: | <i>Smart</i> handling of page references. |
| verbatim: | Flexible version of <code>verbatim</code> environment. |
| xr: | eXternal References. Extend <code>\ref</code> to access <code>\label</code> commands in other documents. |
| xspace: | Smart space command that avoids the common mistake of missing spaces after command names. |