

The langscibook L^AT_EX class

Sebastian Nordhoff

Language Science Press Guidelines

Contents

1	Introduction	1
2	The class	3
3	Requirements	5
3.1	Fonts	5
3.2	Styles	5
3.3	Series definitions	5
4	Creating a book	7
4.1	Creating a monograph	7
4.2	Creating an edited volume	8
4.3	Creating a paper for an edited volume	8
5	Options	11
5.1	Flag options	11
5.1.1	collection	11
5.1.2	draftmode	11
5.1.3	openreview	11
5.1.4	minimal	11
5.1.5	nobabel	11
5.1.6	showindex	11
5.1.7	chinesefont	12
5.1.8	japanesefont	12
5.1.9	hebrewfont	12
5.1.10	arabicfont	12
5.1.11	syriacfont	12
5.2	String options	12
5.2.1	output	12
5.2.2	booklanguage	13
5.2.3	copyright	13
5.3	Metadata commands	13
5.3.1	\BackBody	13

Contents

5.3.2	<code>\BackTitle</code>	13
5.3.3	<code>\BookDOI</code>	13
5.3.4	<code>\ChapterDOI</code>	13
5.3.5	<code>\dedication</code>	14
5.3.6	<code>\lsISBNdigital</code>	14
5.3.7	<code>\lsISBNhardcover</code>	14
5.3.8	<code>\lsISBNsoftcover</code>	14
5.3.9	<code>\lsSeries</code>	14
5.3.10	<code>\lsSeriesNumber</code>	14
5.3.11	<code>\lsID</code>	14
5.4	Overrides	14
5.4.1	<code>\lsImpressionCitationAuthor</code>	15
5.4.2	<code>\lsImpressionCitationText</code>	15
5.4.3	<code>\papernote</code>	15
5.4.4	<code>\lsChapterFooterSize</code>	15
5.4.5	<code>\includespinelogo</code>	15
5.4.6	<code>\includestoragelogo</code>	15
5.4.7	<code>\includepublisherlogo</code>	15
5.4.8	<code>\includechapterfooterlogo</code>	15
5.4.9	<code>\publisherstreetaddress</code>	16
5.4.10	<code>\publisherurl</code>	16
5.4.11	<code>\storageinstitution</code>	16
5.4.12	<code>\githubtext</code>	16
5.4.13	<code>\paperhivetext</code>	16
5.4.14	<code>\lsURL</code>	16
5.5	Command redefinitions	16
5.5.1	<code>\CoverTitleSizes</code>	16
5.5.2	<code>\lsBackBodyFont</code>	17
5.5.3	<code>\lsBackTitleFont</code>	17
5.5.4	<code>\lsCopyright</code>	17
5.5.5	<code>\lsCoverAuthorFont</code>	17
5.5.6	<code>\lsCoverSubTitleFont</code>	17
5.5.7	<code>\lsCoverTitleFont</code>	17
5.5.8	<code>\lsEditorPrefix</code>	17
5.5.9	<code>\lsEditorSuffix</code>	17
5.5.10	<code>\lsLanguageIndexTitle</code>	18
5.5.11	<code>\lsNameIndexTitle</code>	18
5.5.12	<code>\lsSubjectIndexTitle</code>	18
5.5.13	<code>\lsYear</code>	18

5.6	Additions	18
5.6.1	\lsAdditionalFontsImprint	18
5.6.2	\lsImpressumExtra	18

1 Introduction

This document describes the \LaTeX class langscibook.cls. This class is used for typesetting books with Language Science Press. Language Science Press publishes open access monographs and edited volumes in linguistics.

2 The class

The class is loaded via `\documentclass{langscibook}`. The standard use case is the creation of a book. If used without an `output=` option, the option `output=book` is loaded.

The class provides for the following:

- front cover
- frontispiece
- inside title
- colophon
- table of contents
- chapters
- list of references (per chapter or global)
- name index, subject index, language index
- back title
- ISBN
- DOI (per book and per chapter)

3 Requirements

3.1 Fonts

The class uses the fonts Libertinus, Arimo and DejaVu. These have to be present on the system.

3.2 Styles

A couple of additional style files come with the class. Documents using this class will compile without them, but in order to typeset books for Language Science Press, these packages should be loaded as well. These packages are

- `langsci-affiliations.sty`: Parse author affiliations
- `langsci-bidi.sty`: Package for typesetting right-to-left text
- `langsci-gb4e.sty`: Package for linguistic examples
- `langsci-lgr.sty`: The glosses defined in the Leipzig Glossing Rules
- `langsci-optional.sty`: Further commands useful for some typical books
- `langsci-subparts.sty`: adds an additional sectioning level between part and chapter
- `langsci-tbls.sty`: Package for the textbook series Textbooks in Language Sciences

3.3 Series definitions

The metadata for LangSci book series are stored in `langsci-series.def`. For new series, the ISSN field of `langsci-series.def` might have to be updated.

4 Creating a book

The easiest way to start a book is to download the skeletons from <http://langsci-press.org/templatesAndTools>. Sample documents for monographs, edited volumes and chapters in edited volumes are provided in the folder `examples/` as well.

4.1 Creating a monograph

Load the class. Make sure the following metadata values are set with the metadata commands listed in §5.3:

- author
- title

Provide the following additional information if necessary:

- series
- series number
- all ISBNs
- BookDOI
- ID
- blurb (back body)
- subtitle
- backtitle
- dedication
- list of proofreaders

4 Creating a book

- list of typesetters
- list of illustrators
- license other than CC-BY
- list of additional fonts

4.2 Creating an edited volume

Proceed as for a monograph, but use the option `collection`. Use `\author` for the editor(s). Chapters are included via `\includepaper{}`. Set the bibliography resource for all papers in the main file.

4.3 Creating a paper for an edited volume

Use the output option `paper`. Provide the following metadata in the preamble:

- `\author` (with `\affiliation`)
- `\title[short]{long}`
- `\abstract` (optional)

You might want to use `\shorttitalerunninghead` for chapters with very long titles.

Papers can be compiled standalone. You can use the command `\papernote` in the preamble of the paper to adjust the text displayed in the footer. This can be embedded in a conditional as follows (assuming your chapter source file is in a subfolder of the folder containing your main file):

```
\IfFileExists{../samplevolume.tex}{%adjust to name of your master file
  \papernote{\scriptsize\normalfont
    To appear in:
    Change Volume Editor.
    Change volume title.
    Berlin: Language Science Press. [preliminary page numbering]
  }
  \pagenumbering{roman}
  \setcounter{chapter}{23}%adjust the chapter number
  \addtocounter{chapter}{-1}
}{}
```

4.3 Creating a paper for an edited volume

This will set your chapter number to 23 when compiled standalone (rather than 1) and will display text in the chapter footer.

5 Options

The class has flag options to toggle certain behaviours and string options to set metadata values.

5.1 Flag options

5.1.1 `collection`

Make the book an edited volume

Default value: `false`

5.1.2 `draftmode`

Switch to draft mode (adds: draft stamp, indication of overlong lines, date)

Default value: `false`

5.1.3 `openreview`

Switch to open review mode

Default value: `false`

5.1.4 `minimal`

Load a very bare class optimized for compilation speed

Default value: `false`

5.1.5 `nobabel`

Do not use the Babel package in the class

Default value: `false`

5.1.6 `showindex`

Show indexed terms in margin

Default value: `false`

5 Options

5.1.7 **chinesefont**

Load fonts for Chinese and update font info in colophon

Default value: false

5.1.8 **japanesefont**

Load fonts for Japanese and update font info in colophon

Default value: false

5.1.9 **hebrewfont**

Load fonts for Hebrew and update font info in colophon

Default value: false

5.1.10 **arabicfont**

Load fonts for Arabic and update font info in colophon

Default value: false

5.1.11 **syriacfont**

Load fonts for Syriac and update font info in colophon

Default value: false

5.2 String options

5.2.1 **output**

Different output formats

Default value: book

- **book**: The book with frontcover and backcover
- **paper**: Contribution to edited volume
- **minimal**: Optimised for speed. Some features might not work. Useful for drafts.
- **guidelines**: Choose color grey; condense frontmatter

5.2.2 **booklanguage**

Load babel for the specified language and change the custom headers for list of references and indexes

Default value: english

5.2.3 **copyright**

The license chosen

Default value: CC-BY

5.3 **Metadata commands**

The following commands are used to indicated metadata.

5.3.1 **\BackBody**

Text to be printed on the back cover

Default value: `Europan lingues es membres del sam familie. Lor separat existentie es un myth. Por scientie, musica, sport etc, litot Europa usa li sam vocabular. Li lingues differe solmen in li grammatica, li pronounciation e li plu commun vocabules. Omnicos directe al desirabilite de un nov lingua franca: On refusa continuar pagar custosi traductores.`

5.3.2 **\BackTitle**

Title on back cover

Default value: same as on front cover

5.3.3 **\BookDOI**

DOI for the book

Default value: ??

5.3.4 **\ChapterDOI**

DOI for a chapter

Default value: ??

5 Options

5.3.5 \dedication

A dedication

Default value: void

5.3.6 \lsISBNdigital

ISBN for the digital version

Default value: 000-0-000000-00-0

5.3.7 \lsISBNhardcover

ISBN for the hardcover version

Default value: 000-0-000000-00-0

5.3.8 \lsISBNsoftcover

ISBN for the softcover version

Default value: 000-0-000000-00-0

5.3.9 \lsSeries

The series this book appears in. Use the acronyms found in `langsci-series.def`

Default value: eotms

5.3.10 \lsSeriesNumber

Position of the book in its series

Default value: ??

5.3.11 \lsID

The numerical LangSci ID, used for various URLs

Default value: 000

5.4 Overrides

The following commands allow to override further default settings:

5.4.1 `\lsImpressionCitationAuthor`

How the author name should be displayed in the impressum

Default value: Automatically inferred from `\author{}`, but sometimes things go wrong

5.4.2 `\lsImpressionCitationText`

Customize the full citation as displayed in the colophon. Useful for second editions

Default value: Automatically inferred from `\author{}` and `\title{}`

5.4.3 `\papernote`

Text displayed in the footer of chapters

Default value: Automatically inferred from volume and chapter metadata

5.4.4 `\lsChapterFooterSize`

Font size for chapter footers

Default value: `\small`

5.4.5 `\includespinelogo`

The logo to be put on the spine

Default value: `void`

5.4.6 `\includestoragelogo`

The logo of the archiving institution

Default value: `void`

5.4.7 `\includepublisherlogo`

The publisher's logo in the impressum

Default value: `void`

5.4.8 `\includechapterfooterlogo`

The logo to be used in chapter footers

Default value: `void`

5 Options

5.4.9 `\publisherstreetaddress`

the physical address of the publisher

Default value: void

5.4.10 `\publisherurl`

The web address of the publisher

Default value: void

5.4.11 `\storageinstitution`

Where the book is archived

Default value: void

5.4.12 `\githubtext`

Where the tex code of the book can be found

Default value: void

5.4.13 `\paperhivetext`

Where the book can be found on PaperHive

Default value: void

5.4.14 `\lsURL`

Where the book can be found on the publisher's site

Default value: void

5.5 Command redefinitions

Redefine the following commands to further alter the appearance:

5.5.1 `\CoverTitleSizes`

Set custom fontsize #1 and baselineskip #2 for title on cover

Default value: 52pt, 16.75mm

5.5.2 **\lsBackBodyFont**

Font used for text on back cover
Default value: main font

5.5.3 **\lsBackTitleFont**

Font used for title on back cover
Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize{25pt}{10mm}\selectfont`

5.5.4 **\lsCopyright**

Choice of licence
Default value: CC-BY

5.5.5 **\lsCoverAuthorFont**

Font for author/editor on cover
Default value: `\fontsize{25pt}{12.5mm}\selectfont`

5.5.6 **\lsCoverSubTitleFont**

Font for the subtitle
Default value: `\sffamily\addfontfeatures{Scale=MatchUppercase}
\fontsize{25pt}{10mm}\selectfont`

5.5.7 **\lsCoverTitleFont**

Font for the title
Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize52pt17.25mm\selectfont`

5.5.8 **\lsEditorPrefix**

How editors are indicated on title page. Useful for localization.
Default value: `\LARGE Edited by\`

5.5.9 **\lsEditorSuffix**

How editors are indicated in the colophon
Default value: `(ed.)/(eds.)`

5 Options

5.5.10 `\lsLanguageIndexTitle`

The title of the language index. Change this for non-English works
Default value: Language index

5.5.11 `\lsNameIndexTitle`

The title of the name index. Change this for non-English works
Default value: Name index

5.5.12 `\lsSubjectIndexTitle`

The title of the subject index. Change this for non-English works
Default value: Subject index

5.5.13 `\lsYear`

Year of publication
Default value: `\the\year`

5.6 Additions

5.6.1 `\lsAdditionalFontsImprint`

Add additional fonts to the list of fonts in the colophon
Default value: void

5.6.2 `\lsImpressumExtra`

for legal notes required for revised theses (“... in fulfillment of ...”)
Default value: void